

PR:801 Seiko DPU-414 Printer for optimus (80 columns)

In combination with the optimus family of sound level meters, the PR:801 portable printer offers the capability to print noise survey results directly whilst in the field.



- Proven, reliable 4 " portable direct thermal printer
- Highly cost effective printing solution
- Choice of Serial and Parallel connectivity options
- RoHS Compliant

Product Specifications		
Model	DPU-414-40B, DPU-414-41B	
Printing	Method	Thermal serial dot printing
	Number of dots/line	9 x 320
	Paper width (mm)	112
	Printing width (mm)	89.6
	Max Speed (character/sec)	52.5
	Paper path	Curved
	Character matrix (H x W dots)	9 x 7
	Character size(H x W mm)	2.5 x 1.9, 2.5 x 0.9 (Condensed)
	Number of columns	40, 80(Condensed)
Character type	Extend Graphics Character set, Alphanumeric, International Characters, Katakana Character set	
Power supply(V)	Specified AC adapter, Ni-MH Battery	
Battery	Without(option)	
Interface	Parallel (36pins Amphenol), Serial (9pins D-SUB)	
Input buffer	28Kbytes	
Command	ESC/P * conformity	
Cutting	Tear bar	
Operating	Temperature (°C)	0 to 40
	Humidity (%RH)	30 to 80(Non condensing)
Service life (line)	500,000 **	
Dimensions (W x D x H mm)	160.0 x 170.0 x 66.5 (printer unit only) ***	
Mass (g)	Approx.580(without Battery)	
Compliance	FCC, CE, VCCI	
Option	AC Adapter	PW-C0725-W1-U
	Battery Pack	BP-4005-E

Specification subject to change without notice

